

**DESCRIPTION**

- The Turnatip Kit utilises the same Carbide insert as the Airless Tip but with a Brass housing to fit a Turnaflo adaptor.
- The Brass housing is bonded to the Carbide insert and is slotted in the orifice area. The slot is also utilised for orientation purposes by using a special alignment tool.
- Each Turnatip Kit is supplied with grub screws, for both Delavan and competitive units, and an alignment tool.
- The Turnatip number is stamped on the Brass housing for ease of identification e.g.D2.
- The Turnatip is flow tested and pattern width checked in the same way as the Airless Tip.



**TECHNICAL DATA**

TURNATIP NUMBER	AIRLESS TIP REF.	EQUIV. ORIFICE	PATTERN WIDTH	FLOW RATE	TURNATIP NUMBER	AIRLESS TIP REF.	EQUIV. ORIFICE	PATTERN WIDTH	FLOW RATE	TURNATIP NUMBER	AIRLESS TIP REF.	EQUIV. ORIFICE	PATTERN WIDTH	FLOW RATE						
		Inches	Inches				Inches	Inches				Inches	Inches							
X-2	C515	0,005	3	0,02	F-2	C1615	0,016	4	0,19	K-2	C2425	0,024	7	0,42						
X-3	C525		5		F-3	C1625		6		K-3	C2440		9							
X-4	C540		7		F-4	C1640		8		K-4	C2450		12							
A-2	C715	0,007	3	0,4	F-5	C1650		10		K-5	C2465		15							
A-3	C725		5		F-6	C1665		12		K-6	C2473		17							
A-4	C735		6		F-7	C1673		14		K-7	C2480		18,5							
A-5	C740		7		F-8	C1680		15		K-8	C2495		21							
B-2	C915	0,009	3	0,06	F-9	C1695		17		L-2	C2625		7		0,026	7	0,50			
B-3	C925		5,5		G-2	C1825	6	L-3	C2640	9										
B-4	C940		7		G-3	C1840	8,5	L-4	C2650	12										
B-5	C950		8,5		G-4	C1850	10	L-5	C2665	15										
B-6	C965	10	G-5	C1865	13	L-6	C2680	18,5												
C-2	C1115	0,011	3	0,08	G-6	C1880	15	L-7	C2695	21	0,029	7	0,63							
C-3	C1125		5,5		G-7	C1895	17	M-2	C2925	7										
C-4	C1140		7		H-2	C2025	6	M-3	C2940	9										
C-5	C1150		8,5		H-3	C2040	8,5	M-4	C2950	12										
C-6	C1165		10		H-4	C2050	10	M-5	C2965	15										
C-7	C1180	11,5	H-5	C2060	12	M-6	C2973	17	0,031	15	0,75									
D-2	C1315	0,013	3	0,12	H-6	C2065	14	M-7		C2980		18,5								
D-3	C1325		5,5		H-7	C2080	16	M-8		C2995		21,5								
D-4	C1340		8		H-8	C2095	18	N-2		C3140		9								
D-5	C1350		9		J-2	C2125	6	N-3		C3150		12								
D-6	C1365		11		J-3	C2140	8,5	N-4		C3165		15								
D-7	C1380		13		J-4	C2150	11,5	N-5		C3180		18,5								
D-8	C1395		14		J-5	C2165	15	N-6		C3195		21,5								
E-2	C1515		0,015		4	0,16	J-6	C2180	17	P-2	C3640	9	0,036	9	1,0					
E-3	C1525	6		J-7	C2195		19	P-3	C3650	12										
E-4	C1540	8		Flow rates are indicated in US galls/min (water) at an operating pressure of 1000 PSIG (69 Bar.G.).																
E-5	C1550	10														P-4	C3665	15		
E-6	C1565	12														P-5	C3680	18,5		
E-7	C1580	14														P-6	C3695	21,5		
E-8	C1595	15,5														P-7	C36110	24		

**HOW TO ORDER**

Turnatip kit type  
**TURNATIP KIT C2473**