

DESCRIPTION

- Full cone spray pattern with uniform droplet distribution
- Fine atomization with low volume flow
- 1/8" BSPT Male Thread
- Spray angles : 45°, 60° and 90°
- Optionally with filter
- Materials: brass, SS303, SS316




SPECIFICATIONS

TYPE	Thread	Flow Rate (lpm) @ Pressure (Bar)								
		0,35	0,7	1	1,5	2	3	4	6	7
3	200	0,88	7,4	8,7	10,4	11,9	14,2	16,2	18,9	20,7
4	200	1,30	9,9	11,6	13,9	16,0	19,0	21,7	25,3	27,7
5	200	1,86	12,3	14,4	17,3	19,9	23,7	27,0	31,5	34,6
6	100	2,60	14,8	17,3	20,7	23,9	28,4	32,4	37,8	41,5
7	100	3,10	17,3	20,3	24,2	27,9	33,2	37,8	44,2	48,5
8	100	3,95	19,7	23,1	27,7	31,8	37,9	43,2	50,4	55,3
9	100	4,27	22,2	26,0	31,2	35,9	42,7	48,7	56,8	62,3
10	100	5,90	24,6	28,9	34,6	39,8	47,4	54,0	63,0	69,2
12	100	7,20	29,6	34,7	41,5	47,8	56,9	64,9	75,7	83,1
14	100	8,13	34,5	40,5	48,5	55,8	66,4	75,4	88,3	97,0
16	50	8,33	39,5	46,3	55,4	63,8	75,9	86,5	101,0	111,0
18	50	9,29	44,4	52,0	62,3	71,7	85,3	97,2	113,4	125,0
20	50	12,00	49,3	57,8	69,2	79,6	94,8	108,0	126,0	138,0
25	50	13,50	61,9	72,6	86,9	100,0	119,0	136,0	158,0	174,0
30	50	15,35	73,8	86,6	104,0	119,0	142,0	162,0	189,0	207,0

DIMENSIONS

Thread	Male thread without filter		
	SW	L	LG
1/8"	11	17.5	7



HOW TO ORDER

1/8" BLM Type Material
1/8" BLM 30 SS303